



Electrical Safety Kit

CZ-53-R/2



Kit especially designed for safety electrical interventions.

Maximum operating voltage: 36 kV AC

COMPOSITION with quantity for each reference

Reference	Description	Dimensions/ Weight
951891	1 moulded case made of two parts : the red cover is an insulating platform	Height 220 mm - 3,7 kg
MT-830-P	1 yellow telescopic stick	Lenght 1,5 m
CC-127-CS-C	1 hook fitted with a voltage detector (127 V à 90 kV) sound and luminescent (delivered with 4 LR6 batteries)	0,7 kg

COMPOSITION with quantity for each reference

Reference	Description	Dimensions/ Weight
CZ-60	1 insulated cable cutter - For cables Ø max 26 mm - Maximum opening 30 mm	Lenght 63 cm - 2,2 kg
CG-4-10-NR	1 pair of insulating gloves (compliant with IEC 60903)	Length 360 mm
952120	1 talcum bottle for the gloves maintenance	
CG-36/2	1 protection case for the gloves class 2 to 4	460 x 200 x 90 mm - 225 g
MV-137-45	1 pair of insulating boots - Size 45 (CE0120 / EN ISO 20345)	
AT-5005	1 delimiting adhesive tape « Yellow and black »	Lenght 100 m - Width 50 mm
	1 Instructions for use in English	
	1 poster "First aid for electric shock victims" in English	

MAINTENANCE

- Yearly check recommended for every component.
- For the gloves whose bag has been opened, the control should be done every 6 months as recommended in the Annex G of NF EN 60903 standard.

DIMENSIONS / WEIGHT

- Dimensions: 710 x 570 x 240 mm.
- Weight: 18,5 kg.